



Technical data

		Towair 200	Towair 500	Arch	Clear Towair	Cone
Mechanical						
	Unit					
Base diameter	cm/ ft.	80/ 2.62	80/ 2.62	80/ 2.62	80/ 2.62	80/ 2.62
Length of the envelope	m/ ft.	2/ 6.55	5/ 16.4	3.1x5/ 10.2x16.4	0.8/ 2.62 or 1.6/ 5.24	2/6.6 or 3/9.8 or 4/13 or 5/16.4
Average set up time	mn	10	10	15	10	10
Printable		yes	yes	no	no	yes
Internal pressure	mb	0.5 to 1.5	0.3 to 1	0.5 to 2	1 to 2	0.5 to 1.5
Electrical						
Number of lamps		2	0	0	0	0
Type of lamps		halogen UV stop	-	-	-	-
Lamp power	W	2 x 250	-	-	-	-
Power supply	W	650	maxi 1350	maxi 2 700	maxi 1350	maxi 1350
Voltage	V	230/110	230/110	230/110	230/110	230/110
Power cable		3G1.5	3G1.5	3G1.5	3G1.5	3G1.5
Type of lamp holder		E27/E26	-	-	-	-
Average lamp life	h	1 500	-	-	-	-
Power supply protection	A	10/12.5	10/12.5	10/12.5	10/12.5	10/12.5
Safety						
Fire retardement		M1	M1	M1	no	M1
Wind speed resistance	km/h / mph	20/ 12.5	indoor	10/ 6.25	60/ 37.5	20
Global protection rating		IP 43	IP 43	IP 43	IP 43	IP 43
Noise level (at 1m/ 3.3Fft.)	dB	60	60	60	60	60
Packaging						
Type		Cardboard box	Cardboard box	Cardboard box	Cardboard box	Cardboard box
Dimensions	cm	80 x 84 x 27	80 x 84 x 27	80 x 84 x 27	80 x 84 x 27	80*84*27
	ft.	2.62 x 2.75 x 0.88	2.62 x 2.75 x 0.88	2.62 x 2.75 x 0.88	2.62 x 2.75 x 0.88	2.62 x 2.75 x 0.88
Gross weight	kg/ lbs	10/ 22	10/ 22	20/ 44	10/ 22	10/ 22
Option		bag	bag	bag	bag	bag

